

PK 120/42 Hydraulic crimping head 10 - 400 mm<sup>2</sup>

- ▶ Large crimping range up to 400 mm<sup>2</sup>
- ▶ C-head with large 42 mm opening width
- ▶ Up to 60% less crimping operations due to wide crimping compared with 6 t tools

## Characteristics

- For interchangeable dies, series 13, wide crimping
- Crimping head with quick coupling, under no pressure, rotates 360°
- For connecting to hydraulic pumps with 700 bar operating pressure for best possible crimping results

Technical data	
Crimping force	130 kN
Stroke / opening width	42 mm
Crimping range	10 - 400 mm <sup>2</sup>
Operating pressure	max. 700 bar
Weight	4.5 kg

Item	Part No.	
Hydraulic crimping head 10 - 400 mm <sup>2</sup>	<b>PK12042</b>	
Scope of supply	Part No.	Page
Carrying bag	TT2	217

13  
KLAUKETHK 120 Hydraulic crimping tool for workbench mounting 10 - 400 mm<sup>2</sup>

- ▶ Large crimping range up to 400 mm<sup>2</sup>
- ▶ For workbench mounting
- ▶ BG-compliant version
- ▶ Up to 60% less crimping operations due to wide crimping compared with 6 t tools

## Characteristics

- For interchangeable dies, series 13, wide crimping
- Quick coupling
- For connecting to hydraulic pumps with 700 bar operating pressure for best possible crimping results

Technical data	
Crimping force	120 kN
Crimping range	10 - 400 mm <sup>2</sup>
Operating pressure	max. 700 bar
Weight	12 kg
Dimensions	H x W x D: 285 x 160 x 110 mm

Item	Part No.
Hydraulic crimping tool for work bench mounting 10 - 400 mm <sup>2</sup>	<b>THK120</b>

13  
KLAUKE