

PK 22 Hydraulic crimping head 6 - 300 mm²



22
Klauke



- ▶ Large crimping range up to 300 mm²
- ▶ Slim crimping head - ideal when space is critical

Characteristics

- For interchangeable dies, series 22, narrow crimping
- Closed crimping head with quick coupling, flip top style, under no pressure, rotates 360°
- For connecting to hydraulic pumps with 700 bar operating pressure for best possible crimping results

Order info

- Also available for "W" crimping dies (UL certified), part number appendix "W"

Technical data		
Crimping force	60 kN	
Stroke / opening width	17 mm	
Crimping range	6 - 300 mm ²	
Operating pressure	max. 700 bar	
Weight	3.0 kg	
Item	Part No.	
Hydraulic crimping head 6 - 300 mm ²	PK22	
Scope of supply	Part No.	Page
Carrying bag	TT2	217

THK 22 Hydraulisches Presswerkzeug zur Tischmontage 6 - 300 mm²



22
Klauke



- ▶ Large crimping range up to 300 mm²
- ▶ For connecting to hydraulic pumps with 700 bar operating pressure for best possible crimping results

Characteristics

- For interchangeable dies, series 22, narrow crimping
- Quick coupling
- For workbench mounting
- BG-compliant version

Technical data		
Crimping force	60 kN	
Crimping range	6 - 300 mm ²	
Operating pressure	max. 700 bar	
Weight	8.8 kg	
Dimensions	H x W x D: 220 x 160 x 120 mm	
Item	Part No.	
Hydraulic crimping tool for work bench mounting 6 - 300 mm ²	THK22	