

PK 45 Hydraulic crimping head 120 - 1000 mm²

45

45 ton









- ▶ Very large crimping range to 1000 mm²
- ▶ Sturdy construction for safe working
- ▶ For connecting to hydraulic pumps with 700 bar operating pressure for best possible crimping results

Characteristics

- For interchangeable dies, series 45, wide crimping
- Crimping head with quick coupling, under no pressure, rotates 360°

Technical data		
Crimping force	450 kN	
Crimping range	120 - 1000 mm ²	
Operating pressure	max. 700 bar	
Weight	10.3 kg	
Height	265 mm	
Item	Part No.	
Hydraulic crimping head 120 - 1000 mm ²	PK45	
Scope of supply	Part No.	Page
Carrying bag	TT2	217

Available dies for Series 45 for PK 45

Suitable for	Connection material	Crimping range mm ²	Crimp profile	Page
Compression cable lugs and connectors acc. to DIN - Cu				
Compression cable lugs (DIN 46235) and connectors (DIN 46267, part 1) Cu		120 - 1000		455
Compression cable lugs and connectors acc. to DIN - Al				
Compression cable lugs and connectors acc. to DIN - Al		150 - 500		455
Compression joints for full tension connections of Aldrey cables acc. to DIN EN 50182, Al conductors DIN EN 50182, 150 - 300 mm ²				
		150 - 300		455

PK 1000 Hydraulic crimping head, 100 t, up to 1600 mm²

100

100 ton

- ▶ Single-acting crimping head for connecting to hydraulic pumps with 700 bar operating pressure
- ▶ Compact, simple design
- ▶ Extremely high crimping force

Characteristics

- For interchangeable dies (outer: to IZUMI standard EP-100W, inside: DIN standard or customer request)
- Nickel-plated version
- Quick coupling

Order info

- Also available in country-specific version, part number appendix "C"

Technical data		
Crimping force	1000 kN	
Stroke	25 mm	
Crimping range	up to 1600 mm ²	
Operating pressure	max. 700 bar	
Weight	without dies: 27 kg	
Height	Incl. handles: 365 mm	
Dimensions	Outer diameter: 195 mm	
Item	Part No.	
Hydraulic 100 t crimping head with Cejn coupling	PK1000	