Kwik Stepper™ step bit



- Minimum burr
- Long service life
- Good torque transmission
- Less effort when drilling

Suitable for


- Sheet, pipe, NF metal and plastic

Item	Drilling range dia. mm	Step sizes dia. mm	Total length mm	Number of steps	Shank dia. mm	Part No.
Kwik Stepper™ step bit 3.2 - 12.7 mm	3.2 - 12.7	3.2 / 4.0 / 4.8 / 5.6 / 6.4 / 7.1 / 7.9 / 8.7 / 9.5 / 10.3 / 11.1 / 11.9 / 12.7	80	13	634	**52084123**
Kwik Stepper™ step bit 4.8 - 12.7 mm	4.8 - 12.7	4.8 / 6.4 / 7.9 / 9.5 / 11.1 / 12.7	80	6	6.4	**52084124**
Kwik Stepper™ step bit 22.2 mm	22.2	22.2	85	1	9.5	**52084128**
Kwik Stepper™ step bit 4.8 - 22.2 mm	4.8 - 22.2	4.8 / 6.4 / 7.9 / 9.5 / 11.1 / 12.7 / 14.3 / 15.9 / 17.5 / 19.1 / 20.6 / 22.2	85	12	9.5	**52084129**
Kwik Stepper™ step bit 12.7 - 28.6 mm	12.7 - 28.6	12.7 / 22.2 / 28.6	57	3	9.5	**52084131**
Kwik Stepper™ step bit 22.2 - 34.9 mm	22.2 - 34.9	22.2 / 28.6 / 31.0 / 31.8 / 34.9	73	5	9.5	**52084134**
Kwik Stepper™ step bit 9.7 mm	9.7	Predrilling for Greenlee-Draw stud 9.7	40	1	6.4	**50360183**
Kwik Stepper™ step bit 12.7 mm	12.7	Predrilling for Greenlee-Draw stud 12.7	40	1	6.4	**52084125**
Kwik Stepper™ step bit Pg 7 - 21	Pg 7 - 21	Pg7 / Pg9 / Pg11 / Pg13 / Pg16 / Pg21	90	7	9.5	**52084132**
Kwik Stepper™ step bit ISO 16 - 32	ISO 16 – 32	ISO 16 / 20 / 25 / 32	80	4	9.5	**52084133**
Kwik Stepper™ step bit 19.1 mm	19.1	Predrilling for Greenlee-Draw stud	99	1	9,5	**52084126**
Kwik Stepper™ step bit 12 mm	12	Predrilling for Greenlee-Draw stud	99	1	4,4	**52085453**

Variants	Art.-Nr.
Kwik Stepper™ step bit set consisting of 52084123 + 52084129	52084141
Kwik Stepper™ step bit set consisting of 52084123 + 52084129 + 52084131	52085454

Kwik Stepper™ step bit with ROTASTOP® shaft





- ROTASTOP® guarantees best-possible torque transmission
- Minimal burr
- No slipping in the chuck with ROTASTOP®
- Long service life
- Requires minimum effort when drilling

Suitable for

- Reaming of steel sheets, pipes, non-ferrous metals and plastic

Item	Drilling range dia. mm	Step sizes dia. mm	Total length mm	Number of steps	Shank dia. mm	Part No.
Kwik Stepper™ step bit with ROTASTOP® shaft 4 - 12 mm	4 – 12	4.0 / 5.0 / 6.0 / 7.0 / 8.0 / 9.0 / 10.0 / 11.0 / 12.0	80	9	8.0	**50069845**
Kwik Stepper™ step bit with ROTASTOP® shaft 4 - 20 mm	4 – 20	4.0 / 6.0 / 8.0 / 10.0 / 12.0 / 14.0 / 16.0 / 18.0 / 20.0	67	9	8.0	**50069853**
Kwik Stepper™ step bit with ROTASTOP® shaft 6 - 30 mm	6 – 30	6.0 / 8.0 / 10.0 / 12.0 / 14.0 / 16.0 / 18.0 / 20.0 / 22.0 / 24.0 / 26.0 / 28.0 / 30.0	98	13	10.0	**50069861**
Kwik Stepper™ step bit with ROTASTOP® shaft 6 - 36 mm	6 – 36	6.0 / 9.0 / 12.0 / 15.0 / 18.0 / 21.0 / 24.0 / 27.0 / 30.0 / 33.0 / 36.0	85	11	12.0	**50069870**
Kwik Stepper™ step bit with ROTASTOP® shaft ISO 12 - 40 mm	ISO 12 - 40	For ISO 12 / 16 / 20 / 25 / 32 / 40	110	6	12.0	**50069888**